



Sesam 800

ROBUST RADIO REMOTE CONTROL SOLUTIONS
FOR INDUSTRIAL APPLICATIONS

Sesam 800

Transmitters

- Sesam 800 Keyring
- Sesam 800 Small 3
- Sesam 800 Small 6
- Sesam 800 Medium
- Sesam 800 Large 15
- Sesam 800 Large 99



Receivers

- Sesam 800 Wall receiver
- Sesam 800 Wall receiver with display
- Sesam 800 DIN 3, 1 relay



Built to withstand demanding environments and daily use

- Duplex communication - enables a relay feedback indicator on the transmitter
- Encrypted authentication and duplex communication ensures that only a genuine transmitter with the correct ID can communicate, preventing recording, replay, and protecting against listening attacks
- Protection class IP65 and IP67
- 869,8 MHz GMSK
- Very fast function response time - 50 ms
- 16.7 million unique codes
- Long range (200 m) + range limitation functionality
- Configuration tool simplifies large installations
- Removable memory card for easy storing/copying/back up (Wall receiver LCD)
- Highly durable long-life pushbuttons



Sesam 800 Large 99

- Robust, easy to use transmitter including a shock-protective frame
- 15 easy-to-push high quality buttons – manages more than 1 million button presses
- IP67
- Controls up to 999 receivers
- LCD, 1 row 3 characters
- Supports Group ID coding – transmitters can be organized in groups using the same ID, which simplifies maintenance in large-scale installations
- PIN-code for extra safety (Wall receiver LCD)
- Cassette optional – incl or excl external power input 12-24 V





ÅKERSTRÖMS